

**FireCracker RF Computer Interface/Transceiver
Model CM19A**

Installation Instructions

The CM19A Computer Interface sends and receives Wireless Radio Frequency (RF) signals, and works with X10's MultiView, X-Ray Vision, Vanguard Internet Control Center, Sentinel Internet Control Center, and ActiveHome Pro + all plug-ins and mobile apps. It receives RF commands from X10 motion detectors (sold separately) and communicates these commands to the X10 software. The software interprets these commands and tells the CM19A to transmit the appropriate RF commands to a TM751 Transceiver (sold separately). The CM19A therefore works with the X10 software to automatically turn on lights, appliances, and cameras when X10 motion detectors are tripped.

The CM19A requires Windows ® XP, Windows ® Vista, or Windows ® 7.

IMPORTANT: Install the X10 software BEFORE you connect the CM19A to your PC.

1. Download the desired software application from: www.x10.com/software
2. Install the software following the instructions that came with it.
3. When instructed during the installation process plug the CM19A into any unused USB port.
4. Windows will recognize the CM19A and complete the installation. Refer to the application's help file for additional information.

© Windows is a Registered Trademark of Microsoft Corporation

FCC Statement

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION. **NOTE: NO CHANGES OR MODIFICATIONS MAY BE MADE TO THE UNITS. ANY CHANGES MADE TO THE UNITS WILL VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.**

120 DAY LIMITED WARRANTY x10pro-usa.com (X10PRO-USA), a division of Authinx Inc., warrants this product to be free from defective material and workmanship for a period of 120 days from the original date of purchase at retail. X10PRO-USA agrees to repair or replace, at its sole discretion, a defective product if returned to X10PRO-USA within the warranty period and with proof of purchase. If service is required under this warranty:

Call 1-888-384-0969, visit www.x10pro-usa.com, or email support@x10pro-usa.com



Lamp Module LM465

Can be Dimmed and Brightened from any X10 Controller. Responds to "All lights on". Rated for 300 W. Incandescent only.

Appliance Module - AM486/AM466

Two pin polarized (AM486) or 3 pin grounded (AM466). For controlling an air conditioner, TV, stereo, etc. anywhere in the home. Rated 15A for heaters, coffee pots etc.; 1/3 H.P. for motors; 400W for TVs; 500W for lamps.

Wall Switch Module WS467

For controlling important indoor and outdoor security lights. Replaces your existing wall switch and installs like a regular dimmer. Dimmed/brightened from any X10 Controller. Rated 500W incandescent only.

Split Receptacle Module SR227

Replaces existing wall outlet. The top outlet functions like an Appliance Module, the bottom one is a regular outlet. Rated 15A.

3 - Way Wall Switch Module WS4777

For controlling a light which is controlled by two switches. Same features as WS467.

Wireless Remote Control System RC5000

Lets you control 16 X10 modules from inside or outside your home. Can also dim and brighten Lamp Modules and Wall Switch Modules. Works with the HR12A PalmPad Remote and X10 RF Wall Switches (SS13A)

Universal Module UM506

Isolated contact relay and beeper. Can be set for momentary or continuous operation. Not compatible with X10 security systems.

SocketRocket LM15A

Screws in to an existing light fixture. Controls up to 150W, incandescent only.